



CONDUCTCOAT™ AF-6800 FLOOR FINISH

Description

Ohm-Shield™ AF-6800 protects the costly investment of conductive/dissipative flooring.

It protects floors from discoloring with a UV blocking formula while offering long lasting, high gloss, static dissipative properties. With low VOC level, this product is as safe as it is easy to use.



Application

- Designed for conductive/dissipative tiles
- High Abrasion resistance
- Static Dissipative - low VOC
- 10⁵-10⁹ ohms/sq. resistivity
- No formaldehyde, no phthalates
- High Adhesion
- May be used in clean rooms, pharmaceutical rooms, assembly areas
- Low tribogeneration
- Durable and Long Lasting
- High Abrasion resistance

SAFETY INFORMATION

Product has a low odor, low VOC solvent and safe surfactant system.

Does not contain:

| | | |
|-------------------|------|----------|
| Glycol Ether DE | CAS# | 111-90-0 |
| Formaldehyde | CAS# | 50-00-0 |
| Dibutyl Phthalate | CAS# | 87-74-2 |

| | |
|---------------------|---|
| Health | 1 |
| Flammability | 0 |
| Reactivity | 0 |
| Personal Protection | B |

UL listed

Warranty: Static Solutions, Inc. expressly warrants that for a period of (1) one year from the date of purchase any Static Solutions, Inc. product will be free of defects in materials and will function within its specifications. Within the warranty period, the product will be repaired or replaced at Static Solutions, Inc.'s option with no cost to the customer as long as Static Solutions, Inc. receives notice during the warranty period. Defective products must be shipped prepaid to Static Solutions, Inc.'s factory. Call Static Solutions, Inc. customer service at 508-480-0700 for a return authorization number. Include a copy of the invoice, packing slip, or other proof of purchase.

Warranty Exclusion: The foregoing express warranty is made in lieu of other product warranties express and implied, including merchantability and fitness for a particular purpose which are specifically or indirectly disclaimed. The express warranty will not apply to defects or damage due to neglect, misuse, accidents, alterations, operator error, failure to properly maintain, follow instruction, or failure to clean or repair products.

Limit of Warranty: In no event will Static Solutions, Inc. or seller be responsible or liable for special, incidental or consequential losses or damages, whether based on tort, contract, or the use of or inability to use, the product. Before using the product users shall determine the suitability of the product for their intended use. The users assume all risk and liability whatsoever in connection therewith. Fulfillment of Static Solutions, Inc.'s warranty obligations will be the customer's exclusive remedy and Static Solutions, Inc. and seller's limit of liability for any breach of warranty or otherwise.

Specifications:

| | |
|--------------------------|---|
| Surface Resistance (RTT) | 10 ⁸ -10 ⁹ ohms/sq. @ 100 volts |
| Electrostatic | |
| Decay Time EIA 541 | 0.1 seconds |
| Slip Resistance | |
| ASTM-D2047-5 | 0.5 minimum |
| Percent Solids | 19.0%+/- 0.5% |
| pH | 8.0-9.0 |
| Free Ammonia | None |
| Free Alkali | None |
| Free Acid | None |
| Phosphates | None |
| Color | Milky White (Dries Clear) |
| Odor | Mild |
| Solubility in Water | 100% |
| Freeze/Thaw Stability | 3 cycles |
| Shelf Life | 1 year |
| Flash Point | None |
| Weight Per Gallon | 8.6 lbs./gallon |
| Biodegradable | Yes |
| VOC | 4.52% |

Static Solutions, Inc.

331 Boston Post Road - East
Marlborough, MA 01752, USA
Tel: 508.480.0700
Fax: 508.485.3353

Static Solutions, Inc. Only sells through distributors.
Please call us at 508.480.0700
or log on to our website, www.staticsolutions.com,
or www.staticsolutions.co.uk to find your local distributor.

For additional OHM-SHIELD™ product literature, call or fax the Static Solutions, Inc. sales department

DISTRIBUTED BY:

Static Solutions, Inc.